

LOCTITE[®] SILVER GRADE ANTI-SEIZE

June 2014

PRODUCT DESCRIPTION

LOCTITE[®] SILVER GRADE ANTI-SEIZE provides the following product characteristics:

Technology	Anti-Seize
Chemical Type	Synthetic Grease
Appearance	Aluminum Silver Colored Paste ^{LMS}
Viscosity	Thixotropic
Cure	Non-curing
Application	Lubrication

LOCTITE[®] SILVER GRADE ANTI-SEIZE is a heavy-duty, high temperature, anti-seize lubricant that resists galling and corrosion and reduces wear in heavy pressure applications. This product is used to lubricate and to permit easy disassembly of assemblies exposed to high temperatures, heavy contact pressures in mines, power generation plants, pulp and paper plants, chemical plants, quarries, transportation, water treatment plants and general industry. Typical applications include boiler and oven parts, jet engines, studs, pumps, couplings, splines, bolts, bushings, pipes, flanges and industrial turbines. This product is typically used in applications up to 870 °C.

MIL-PRF-907

LOCTITE[®] SILVER GRADE ANTI-SEIZE meets the performance requirements of Military Specification MIL-PRF-907.

TYPICAL PROPERTIES

Specific Gravity @ 25 °C	1.0 to 1.3 ^{LMS}
Flash Point - See SDS	
Viscosity, Brookfield - RVT, 25°C, mPa·s (cP):	
Spindle TD, speed 2.5 rpm	121,000 to 258,000 ^{LMS}
Penetration, ISO 2137, worked, 1/10 mm	324
Penetration, ISO 2137, unworked, 1/10 mm	312
Drop Point, ISO 2176, °C	232
NGLI Grade	1
Timken OK Load, ASTM D2509, lbs	47
Timken Fail Load, ASTM D2509, lbs	52
Scar Width at failure, mm	0.83
Stress value at failure, N/mm ²	65

TYPICAL PERFORMANCE

An anti-seize lubricant used on a bolt helps to develop greater clamp load for the same torque compared to an unlubricated bolt. An additional benefit is greater uniformity in clamp load among a series of bolts. The relationship between torque and clamp load is expressed in the following equation:

$$T = K \times F \times D$$

T = Torque (N·m, lb.in, lb.ft)

K = Torque coefficient or nut factor, determine experimentally

F = Clamp load (N, lb.)

D = Nominal diameter of bolt (mm, in.)

Torque coefficient, k:	
3/8 x 16 steel nuts and bolts	0.18

Static Coefficient of Friction

The following information shows the static coefficient of friction between controlled mating surfaces subjected to a compressive stress that approximates the bearing stress acting on fastener threads under load (60% of proof for a 3/8-16 Grade 5 steel).

At -54°C (-65F)	0.043
At 20°C (68F)	0.077
At 870°C (1400F)	0.164

TYPICAL ENVIRONMENTAL RESISTANCE

Heat Aging

The following chart shows break and prevail torque values for plain steel 3/8-16 fasteners, degreased, coated, pre-torqued to 40 Nm (30 ft-lbs), held at noted temperatures for 24 hours, cooled to room temperature and disassembled. No signs of galling or seizing were visible.

Temperature (°C)	Break (N-m)	Prevail (N-m)
-55	270	6
22	264	6
535	96	7
760	262	160
870	132	89

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).



Directions for use

1. For best performance part surfaces should be clean and free of grease.
2. Apply a light coating to parts requiring lubrication, assemble.
3. Wipe away any excess compound.
4. **CAUTION:** LOCTITE® SILVER GRADE ANTI-SEIZE is not a high-speed load carrying lubricant and should not be used on ball or roller bearings, or on parts where lubrication is critical.

Loctite Material Specification^{LMS}

LMS dated October 2, 2002. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1

